



污水处理 家庭供水 城市用水 工业用水



一、产品概述 / Product Overview

PC离心泵系列(以下简称电泵), 根据企业标准所规定的性能参数, 并结合本公司多年生产经验而设计的新一代产品。泵结构紧凑、体积小、外形美观、安装占地面积小、运行稳定、使用寿命长、效率高、耗电省、装修方便等优点。并可根据扬程与流量的需要并联使用。本电泵由电动机, 机械密封, 水泵三部分组成, 电机为单相或三相异步电动机; 水泵与电动机间采用机械密封, 电泵转子轴采用优质碳钢材料, 并进行防腐处理, 确保轴有更可靠的机械强度, 可有效地提高轴的耐磨性和耐腐蚀性, 同时也有便于叶轮的维修和拆卸, 泵各固定止口密封处采用“O”形橡胶密封圈作静密封。

PC Centrifugal pump series are the new generation products according to the enterprise standards and with many years of design experience. The pump has the advantages of compact structure. Small volume, beautiful appearance, small install area, stable operation, long service life, high efficiency, low power consumption, convenient installation and maintain etc. The pump is composed of motor, mechanical seal and pump part. With high quality 45# steel shaft, chrome plating processing ensure the strength and corrosion resistance.

二、适用范围 / Application

- 1、适用于城市环保、大棚喷灌、建筑、消防、化工、制药、染料印染、酿造、 电力、电镀、造纸、石油、矿山、设备冷却等。
 - 2、可和任何型号、规格的压滤机配套使用, 将浆料送给滤机进行压滤的最理想配套泵种。
- 1、City environmental protection, greenhouse sprinkler irrigation, construction, fire, chemical, pharmaceutical, printing and dyeing, brewing, electric power, papermaking, electroplating, petroleum, mining, equipment cooling etc.
 - 2、 Can be equipped to any type filter. it is the most ideal supportive pump to filter.

三、型号说明 / Model description



技术参数 / Parameter

型号 Type	流量Q (L/S)	扬程 (m)	最大流量 (m³/h)	最大扬程 (m)	功率 (kW)	电压 (V)	同步转速 (r/min)	配管内径 (mm)
50PC18-28/2.2	18	28	27	32	2.2	380	3000	50
50PC18-34/3	18	34	27	38	3	380	3000	50
50PC18-44/4	18	44	27	49	4	380	3000	50
50PC18-47/5.5	18	47	27	52	5.5	380	3000	50
50PC18-50/7.5	18	50	27	55	7.5	380	3000	50

